Pomona®

Model 5301 & 5521
SMD Grabber® Test Clip Patch Cord



FEATURES:

- Ideal for providing a temporary jumper wire between surface mount devices.

MATERIALS:

SMD Grabber® test clip
Contact - Stainless Steel
Spring – Stainless Steel
Cap – Glass filled nylon. Color matches color of wire
Barrel – Glass filled nylon. Color matches color of wire
Marking: "POMONA GRABBER®"
Finish: Gold plated
Wire: 22 AWG, PVC insulated
Marking: "Model 5301"

RATINGS:

Operating Temperature: +102°C (+216°F) Max.
Voltage: Hand-held testing 33 Vrms/70 Vdc Max.
Hands free testing in controlled voltage environments: 150 WVDC Max.
Current: .5 Amperes

ORDERING INFORMATION: Model 5301-XX-*
XX = Standard Lengths in Inches, 12" and 24"
* = Color, -0 Black, -2 Red
Ordering Example: 5301-12-2 Indicates 12", color is red.

5521 Kit contains 10 pieces of model 5301-24, 1 each of 10 colors.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (,51 mm), .xxx = ± .005" (,127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 425-446-5844 Technical Support: technicalsupport@pomonatest.com
For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com